

ASW019



ASW019 -

'Sleek m Slim'

RFID Access Control System

TECHNICAL SPECIFICATION

- ✦ CPU: 32bit embedded RISC
- ✦ Capacity: 30000 card handle, 50000 logs
- ✦ Verified by: Card, Password+ Card No, Pass word
- ✦ Reader interface: with external controller model 6011A. Frequency 902 MHz - 928 MHz (FCC) 865 zHM - 868 zHM C(E,) Reading range >12 m, Power consumption - 9V DC.
- ✦ Access control function: 50 time zones, 5 groups, 10 combinations, support many fingerprints access, 10A/12VDC relay switch volume or voltage output
- ✦ Alarm Function: dismantlement alarm, threaten alarm, unlock illegally alarm, not block alarm.
- ✦ External alarmed speaker, alarmed light or alarm host connectable, and can alarm incessant to send signal
- ✦ Communication Way: RS485 or TCP/IP
- ✦ Other input: one group door magnet and door open signal input
- ✦ LCD, Voice and Keypad: four lines blue LCD, double LED indicator light, multi-language, and 16 no. Keypad
- ✦ Auto test: Yes
- ✦ Battery Supplier parameter: 12VDC, sleeping current<50mA, working current<400mA
- ✦ Operating: temperature, 35 degree-65degree; humidity, 10%-90%
- ✦ Size: 100*129*40 mm